



ALTO SERVICE ITALIA s.r.l.

Via Calagrande , 9b – via Di Vittorio , 27 – Z.I.

Tel. 0039/0584/969685/969518

Fax 0039/0584/969457

55040 CAPEZZANO PIANORE (Lucca) Italy

Web page: www.altoservice.it

e-mail: altoservice@altoservice.it



M30 – M40

CARRELLO PORTA IMBARCAZIONI MOTORIZZATO SELF-PROPELLED TRAILER FOR BOATS



M30 –M40

CARATTERISTICHE TECNICHE

TECHNICAL CHARACTERISTICS

- Carrello motorizzato semovente
- Radiocomando a distanza
- Gruppi ruota autolivellanti , basculanti e sterzanti
- Gomme piene
- Sollevamenti idraulici anteriori posteriori separati
- Sterzata anteriore - posteriore indipendente
- Parte posteriore aperta
- Candele telescopiche
- Forche rientranti per sollevamento invasature

- Self-propelled trailer
- Remote control
- Self levelling , balancing , steering wheel sets
- Solid tires
- Frontal- rear separated hydraulic lifting
- Frontal – rear separated steering
- Open end design
- Telescopic bars
- Re-entering forks for cradle lifting

				M30	M40
Portata (Ton)	Capacity (Ton)	30	40		
Lunghezza max "A" (mm)	Max lenght "A" (mm)	10715	10715		
Larghezza max "B" (mm)	Max width "B" (mm)	4465	4470		
Larghezza interno "C" (mm)	Inside clear width "C" (mm)	2735	2730		
Sollev. ant - post (corsa) (mm)	Frontal - rear lifting (stroke) (mm)	300	300		
Sterzata ant - post	Frontal - rear separated steering	35°	35°		
Velocità max (km/h)	Max speed (km/h)	3	3		
Pendenza superabile	Gradeability	3%	3%		
Ruote motrici (q.tà)	Motorized wheels (q.ty)	4	4		
Gomma superel. (tipo/q.tà)	Superelastic Tire (mod/q.ty)	27-10-12 (8)	300-15 (8)		
Freni idrost. per servizio (q.tà)	Hydrostatic brakes (q.ty)	4	2		
Freni di emerg. e staz. (q.tà)	Emerg. and park. brakes (q.ty)	-	-		

